








MULTIPURPOSE ELECTRICAL DROP BOLTS										Export Product-list January 2024							
Minilock & Microlock																	
TECHNICAL CHARACTERISTICS Models for recessed mounting. Each solenoi bolt comes with its own counterflange. For surface mounting are available the pertinent BLINDOBOX housing (see page 23).	HEAVY DUTY LOCKING BOLT solid AISI 316 stainless steel Microlock (steel or AISI 303 s. s.)	UNIVERSAL OPERATING VOLTAGE Vdc	CURRENT DRAW mA	BOLT STATUS SENSOR ● 1 SPDT dry contact 1A ○ 1 SPDT dry contact 0,5A	• Timed opening (1÷20 sec) • Control of bolt exit • Interlink (for interlock)	REGOPLUS® DOOR STATUS SENSOR	F = Frontal flange for flush mounting FZ = Long flange for flush mounting L = Bracket for surface mounting	R = Reversible D = Right hand (DIN links) S = Left hand (DIN recths)	SERIE BLUELOCK® (fail-secure) security version = bolt 'out' without power SERIE REDLOCK® (fail-safe) anti-panic version = bolt 'out' with power	Ordering information 							
										MODELS				Q.ty			
														N°			
 Type F  Type L  Type FZ	 ROUND BOLT Ø 15mm stroke 14mm	12/24V	900/450	●	---	---	F	R	MINI-BLUELOCK	0081B2RFU 0081B2RLU 0081B2RFZU							
		12/24V	900/450	●	---	---	L	R	MINI-BLUELOCK								
		12/24V	900/450	●	---	●	FZ	R	MINI-BLUELOCK								
		12/24V	900/450	●	---	---	F	R	MINI-REDLOCK	0083B2RFU 0083B2RLU 0083B2RFZU							
		12/24V	900/450	●	---	---	L	R	MINI-REDLOCK								
		12/24V	900/450	●	---	●	FZ	R	MINI-REDLOCK								
	 SLANTED BOLT Ø 15mm stroke 14mm	12/24V	900/450	●	---	---	F	R	MINI-BLUELOCK	0082B2RFU 0082B2RLU 0082B2(D/S?)FZU							
		12/24V	900/450	●	---	---	L	R	MINI-BLUELOCK								
		12/24V	900/450	●	---	●	FZ	D/S ?	MINI-BLUELOCK								
		12/24V	900/450	●	---	---	F	R	MINI-REDLOCK	0084B2RFU 0084B2RLU 0084B2(D/S?)FZU							
		12/24V	900/450	●	---	---	L	R	MINI-REDLOCK								
		12/24V	900/450	●	---	●	FZ	D/S ?	MINI-REDLOCK								
 Type F  Type L	 ROUND BOLT Ø 8mm stroke 8mm	12V	390	---	---	---	F/L ?	R	MICRO-BLUELOCK	00801A2R(F/L?) 00801A4R(F/L?) 00801B2R(F/L?) 00801B4R(F/L?) 00803A2R(F/L?) 00803A4R(F/L?) 00803B2R(F/L?) 00803B4R(F/L?)							
		24V	200	---	---	---	F/L ?	R	MICRO-BLUELOCK								
		12V	390	○	---	---	F/L ?	R	MICRO-BLUELOCK								
		24V	200	○	---	---	F/L ?	R	MICRO-BLUELOCK								
		12V	390	---	---	---	F/L ?	R	MICRO-REDLOCK								
		24V	200	---	---	---	F/L ?	R	MICRO-REDLOCK								
		12V	390	○	---	---	F/L ?	R	MICRO-REDLOCK								
		24V	200	○	---	---	F/L ?	R	MICRO-REDLOCK								
		Note: See also SLIM-MICROLOCK on page 24															
		ADDITIONAL ANCILLARIES FOR MICROLOCK															
		TWO-SLIDES COUNTER-STRIKES FOR MICROLOCK 		Additional accessory for Microlock electrical drop bolts a - two-slides counter-plate for Microlock "F" version for flush mounting a' - two-slides counter-plate as above but FZ version (20x60mm) including magnet for door status sensor b - two-slides strike block for Microlock "L" version for surface mounting (the strike block is alluminium anodized "silver colour" type).									0080502R 0080502RZ S00809V1RF				
		"TRONIX" VERSION with smart micromodule															
 Version "FZ"	 ROUND BOLT Ø 15mm stroke 14mm	12/24V	900/450	●	●	●	FZ	R	MINI-BLUELOCK	0081B2RFZUT 0083B2RFZUT							
		12/24V	900/450	●	●	●	FZ	R	MINI-REDLOCK								
	 SLANTED BOLT Ø 15mm stroke 14mm	12/24V	900/450	●	●	●	FZ	D/S ?	MINI-BLUELOCK	0082B2(D/S?)FZUT 0084B2(D/S?)FZUT							
		12/24V	900/450	●	●	●	FZ	D/S ?	MINI-REDLOCK								

Note: prices quoted do **not include** key cylinders, handles and other installation accessories. The standard locking counter plate is always supplied with Minilock electrical drop bolts, but for Microlock electrical drop bolt. The electrical drop bolt Minilock and Microlock should be required equipped with additional rod (fitted axially in the rearbody) to provide mechanical release, with extraprice of euro 16,00 each unit.